

ASO

■ Grey



OLE ASO S



OLE ASO D

| | | | |
|------|--------------|------------|---------------------|
| IP65 | 220V 240V | CRI >70 | MADE IN MALAYSIA |
|------|--------------|------------|---------------------|



Landscape Lighting

Features

| | |
|---------------------|----------------------|
| Lumen Maintenance | : L90 @ 60,000 hours |
| Working Temperature | : -40°C ~ 50°C |
| Storage Temperature | : -20°C ~ 80°C |
| Power Factor | : >0.95 at Full Load |
| THD | : <20% at Full Load |

Material

| | |
|--------------|--|
| Casing | : Extrusion aluminum AA 6063-T5 with outdoor epoxy powder coated |
| Cover | : Tempered glass |
| Flange Plate | : Aluminum |
| Dimming | : (Optional) 0-10V / DALI / Timer |

Advantages

It has a versatile light distribution. Can be use by both residential and commercial buildings for security, safety and beauty purposes.



Application

Applicable for Pedestrian Walkway, Car Park, Garden Lighting, Area Lighting and others.

Specifications

| Model No. | Power | Lamp | Input current | Weight | Color | Efficacy | Lumen |
|------------------|-------|-----------|---------------|---------|-------------|----------|---------|
| OLE ASO S-30W-3M | 30W | 1 Module | 0.13A | 17.25kg | 3500K-6000K | 100 lm/W | 3000 lm |
| OLE ASO S-30W-4M | 30W | 1 Module | 0.13A | 21.83kg | 3500K-6000K | 100 lm/W | 3000 lm |
| OLE ASO S-30W-5M | 30W | 1 Module | 0.13A | 26.52kg | 3500K-6000K | 100 lm/W | 3000 lm |
| OLE ASO S-30W-6M | 30W | 1 Module | 0.13A | 31.15kg | 3500K-6000K | 100 lm/W | 3000 lm |
| OLE ASO D-30W-3M | 30Wx2 | 2 Modules | 0.26A | 19.75kg | 3500K-6000K | 100 lm/W | 6000 lm |
| OLE ASO D-30W-4M | 30Wx2 | 2 Modules | 0.26A | 25.18kg | 3500K-6000K | 100 lm/W | 6000 lm |
| OLE ASO D-30W-5M | 30Wx2 | 2 Modules | 0.26A | 28.4kg | 3500K-6000K | 100 lm/W | 6000 lm |
| OLE ASO D-30W-6M | 30Wx2 | 2 Modules | 0.26A | 32.8kg | 3500K-6000K | 100 lm/W | 6000 lm |

Photometric Data



Feature Diagram




LED Module
High performance LED
with high efficiency lens

Casing material
Extrusion Aluminum AA 6063-T5 with
Outdoor Epoxy Powder Coated



LED Module



Aluminum Flange Plate

Landscape Lighting

Dimension

| OLE ASO S | OLE ASO D |
|---|---|
| <p>Wrapping Size: (3M)3015x142x142 / (4M)4015x142x142 / (5M)5015x142x142 / (6M)6015x142x142</p> <p>Flange Plate</p> | <p>Wrapping Size: (3M)3015x142x142 / (4M)4015x142x142 / (5M)5015x142x142 / (6M)6015x142x142</p> <p>Flange Plate</p> |