

ALPHA

Grey



IP65    220V  
240V    CRI  
>70    MADE IN  
MALAYSIA

Features

Lumen Maintenance : L90 @ 60,000 hours  
 Working Temperature : -40°C ~ 50°C  
 Storage Temperature : -20°C ~ 80°C  
 Power Factor : >0.95 at Full Load  
 THD : <20% at Full Load

Material

Casing : Extrusion aluminum AA 6063-T5 with outdoor epoxy powder coated  
 Cover : Acrylic  
 Flange Plate: Aluminum  
 Dimming : (Optional) 0-10V / DALI / Timer

Advantages

It has a versatile light distribution. Can be use by both residential and commercial buildings for security, safety and beauty purposes.



Application

Applicable for Pedestrian Walkway, Car Park, Garden Lighting, Area Lighting and others.

## Specifications

Model No.	Power	Lamp	Input current	Weight	Color	Efficacy	Lumen
OLE ALPHA 1-24W-2M	24W	LED Strip	0.10A	13.5kg	3500K-6000K	67 lm/W	1600 lm
OLE ALPHA 1-48W-3M	48W	LED Strip	0.20A	20.25kg	3500K-6000K	67 lm/W	3200 lm
OLE ALPHA 2-48W-2M	48W	LED Strip	0.20A	15.5kg	3500K-6000K	67 lm/W	3200 lm
OLE ALPHA 2-96W-3M	96W	LED Strip	0.41A	21.97kg	3500K-6000K	67 lm/W	6400 lm


## Photometric Data




Feature Diagram



Casing material  
Extrusion Aluminium AA 6063-T5 with  
Outdoor Epoxy Powder Coated



Front & Back Light / 4 Sided  
Light Emitting Surface



Aluminum Flange Plate

Dimension

OLE ALPHA 1-24W-2M	OLE ALPHA 1-48W-3M
<p>Wrapping Size: 2015x142x142</p> <p>(Front &amp; Back Light Emitting Surface)</p>	<p>Wrapping Size: 3015x142x142</p> <p>(Front &amp; Back Light Emitting Surface)</p>
OLE ALPHA 2-48W-2M	OLE ALPHA 2-96W-3M
<p>Wrapping Size: 2015x142x142</p> <p>(4 Sided Light Emitting Surface)</p>	<p>Wrapping Size: 3015x142x142</p> <p>(4 Sided Light Emitting Surface)</p>