




LED SPOTLIGHT. OLE BL D60



Mounting Plate

OLE BL D60					
Code	OLE BL 0110D60	OLE BL 0108D60	OLE BL 0303D60A	OLE BL 0303D60B	OLE BL 0304D60
Power	LED 1*10W	LED 1*8W	LED 3*3W	LED 3*3W	LED 3*4W
LED Brand	CREE 1304 COB	CREE XM-L	CREE-XP-E2	EPISTAR	EPISTAR
Color	3000K~6000K	RGBW 4in1 DMX512	3000K~6000K	RGBW 3in1 DMX512	RGBW 4in1 DMX512
Beam Angle	18°/24°/38°/60°	15°/30°/45°/60°	6°/12°/25°/40°/60°	15°/30°/45°/60°	15°/30°/45°/60°
Input Voltage	AC240V/DC24V	DC24V	AC240V/DC24V	DC24V	DC24V

- Protection : IP66
- Impact Protection : IK08
- Color Rendering Index (CRI) : >80/90
- Material : Die-Cast Aluminium ADC12
- Connector : IP68 Connector



Optional Applications

<p>274 300/ 500/800/ 1000</p>	<p>300/500/800/ 1000</p>	<p>274</p>	<p>150 104</p>	<p>ø150~ø400</p>
Spike+Pole	Pole	Spike	Pole Mounting	Tree Ring



Optical Accessories



*All LED lighting can refer SPD specifications page 88